

Chemical Compatibility of Nitrile Rubber Products

	Chemical Tested	Rating	Applies to these products:	
А	Aliphatic Hydrocarbons - Kerosene, Etc.	1		
В	Animal & Vegetable Oils	1		
С	Aromatic Hydrocarbons - Benzol, Toluol, Etc.	1		The case of the case
D	Bleach	1		
E	Concentrated Alkali	1		
F	Cutting Oil	1		
G	Denatured Alcohol	1		
Н	Diesel	1	Comfort Flow	Complete Comfort II
I	Dilute Alkali	1		
J	Engine Oil	1		
K	Gasoline	1		
L	Hydraulic Fluid Silicate Ester	1		- 1 July 100
M	Hydraulic Fluid Water Glycol	1		10 miles
N	L.P. Gas, Fuel Oils	1		
0	Lubricating Oils - High Aniline	1		
Р	Lubricating Oils - Low Aniline Point	1	Cuchian Station	DuraCamfort
Q	Mineral Spirits	1	Cushion Station DuraComfor	DuraComfort
R	Muriatic Acid - 30%, 20 Degrees Baume	1		
S	Phosphoric Acid	1		
T	Pine Cleaner	1		
U	Refrigerants, Ammonia	1		
V	Sodium Hydroxide, Rayon Grade, 25%	1		
W	Sulphuric Acid - 30%	1		
Χ	Transmission Fluid	1		
Υ	WD40	1	Hog Heaven	Hog Heaven III
Z	Water	1		
AA	Window Cleaner	1	16000	
BB	Anti-Freeze	2	10 00 000	
CC	Brake Fluid	2		
DD	Calcium Hypochlorite - 12%	2		
EE	Chlorine Bleach - 12.5%	2		
FF	Hydraulic Fluid - Petroleum Base	2		
GG	Steam	2	Safety Scrape Traction Tread	Traction Tread
НН	Butyl Alcohol	3		
II	Isopropyl Alcohol - 99%	3	1 = Little or no effect 2 = Minor to moderate effect 3 = Moderate to severe effect 4 = Not recommended	
JJ	Acetic Acid - 56%	4		
KK	Acetone	4		
LL	Cyclohexane	4		
MM	Refrigerants, Methyl Chloride	4		