





Wet Area Anti-Fatigue Options


Comfort Flow™




Comfort Premier




Comfort Station Max



Traction Tread Grit Mat



Wet Step®



Material	High-density, closed cell nitrile rubber foam	High-density, closed cell nitrile rubber foam	High-density, closed cell nitrile rubber foam	Nitrile rubber with silicon carbide grit inserts	High-density, closed cell nitrile rubber foam
Thickness	3/8" (0.375)	1/2" (0.50)	7/16" (0.438)	7/32" (0.219)	1/4" (0.25)
Slip Resistance (Static Coefficient of Friction*)	Dry 1.00 Wet 0.91	Dry 0.96 Wet 0.82	Dry 0.96 Wet 0.80		Dry 0.99 Wet 0.82
Drainage Holes	✓		✓ available with or without holes	✓	✓
Grease/Oil Proof	✓	✓	✓	✓	✓
Chemical Resistant	✓	✓	✓	✓	✓
Welding Safe	✓	✓	✓		✓
Anti-Microbial	✓	✓	✓	✓	✓
Autoclavable	✓	✓	✓		✓
Available Sizes	2' x 3' 3' x 9' 3' x 5' 4' x 6' Also available in modular and linkable configurations.	2' x 3' 3' x 5' 3' x 4' 4' x 6'	2' x 3.2' 3.2' x 16.1' 4' x 12.3' 3.2' x 5.3' 3.2' x 20.1' 4' x 16.1' 3.2' x 8.3' 4' x 5.9' 4' x 20.1' 3.2' x 12.3' 4' x 8.3'	3'x5'	17" x 24" 3' x 10' 2' x 3' 3' x 20' 3' x 5' Custom 3' widths up to 20' in length are available.
Color Options	Black	Black	Black	Black	Blue or Grey